



<b>Anziehvorschrift für Zylinderkopf</b>	<b>460.410</b>	 Das Original
<b>Tightening Instructions for Cylinder Head</b>		
<b>Instructions de serrage pour culasse</b>		
<b>Prescripciones de apriete para culatas</b>		
	passend für / suitable for adaptable à / adaptable a	<b>Renault</b>

Schraubenkopf / Head shape      Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete  
Tête de vis / Cabeza de tornillo



649.390  
M10x1,5x123

Anziehen/ Tightening/ Serrage/ Apriete	✳	Pos. 1-10: 40 Nm
	➤	Pos. 1-10: 83° ± 2°
	☐	Pos. 1-10: 40 Nm
	➤	Pos. 1-10: 93° ± 2°
	➤	Pos. 1-10: 93° ± 2°

Zeichenerklärung / Explanations / Explication / Explicacion

✳	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
☐	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro

**Motortyp / Engine type / Type de moteur / Tipo de motor**

Ø: 78,5 mm;  $\pm$ : 0,7 mm

Mot: H4J 700 - 1.4 TCe

Renault Grand Scénic III, Scénic III  
Megane III

ElringKlinger AG, Max-Eyth-Str.2  
72581 Dettingen / Erms. Tel. 07123/724 601

**\*460.410\***